



SMART PRINTING SOLUTIONS

Technical Data Sheet

Parameters	Description	Storage
Item	SPS6130H	When stored in the original, unopened containers in a dry and cool place, the shelf life is as follows: (Shelf-life) In unopened original packaging: 12 months.
Material Base	Polyolefin	Packaging Specification
Core Application Categories	PO	For granular hot melt adhesive products: Bagged specifications: 25kgs/bag and 28kgs/bag Bulk cargo (unpackaged): Minimum palletizing quantity: 500kg per pallet. Optimal freight efficiency: 1MT (1,000kg) per pallet for bulk shipments.
Specific Application Directions	Used for bonding of paper product packaging.	20ft container palletized capacity: 16MT (16,000.00).
Shape	Granular	
Color	White	Additional information
Melting Viscosity	About 1500mPa.s/160°C	1. Wear protective gloves and clothing to ensure safety due to high temperatures during product use.
Softening Point	115±5°C	2. Keep the melt tank lid tightly closed at all times to prevent debris from falling into the tank and affecting the usage effect.
Solid Content	100%	3. The above information is provided based on our knowledge and experience. If materials or working conditions change, conduct thorough testing or contact our technicians for advice.
Toxicity	Non-toxic	
Storage Life	12 months	
Recommended Working Temperature	140~170°C	

SMART PRINTING SOLUTIONS
ZAC MBAO CITE CHEIKH FAYE VILLA 352/ DP

NINEA : 009291593--- Tel : (221) 77 572 57 86

N° Compte : SN100 01022 005051960003 93 BANK OF AFRICA Dakar-SENEGAL

Email : smartprintingsolutionsenegal@gmail.com